



Lounge chair with upholstered seat and backrest and 4 steel legs available in different colors.

0.75 m³ 26.49 Ft 21.7 kg 47.84 Lbs

	Backrest height	Seat height	Arm height	Width	Depth
Measures (mm)	820	450	685	840	790

Frame	4-legged steel tube base
Seat	Solid pine structure with polypropylene elastic straps with an upholstered cushion with flexible fire resistant polyurethane foam with density between 25 kg/m ³ and 40 kg/m ³ .
Back	Solid pine structure with polypropylene elastic straps with an upholstered cushion with flexible fire resistant polyurethane foam with density between 25 kg/m ³ and 40 kg/m ³ .
Arms	Estructura de madera maciza de pino con cincha elástica de polipropileno recubierto de espuma flexible ignífuga de densidad entre 25kg/m ³ y 40kg/m ³ .
Accessories	USB charging system in upholstery, personalize inner seam
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.
Upholstery	

Leather / Piel

- L1** High grade cow leather
Piel de vaca de 1ª categoría
- L3** Polished full grain leather
Piel de vaca pulida
- L6** Aniline leather batique-effect.
Scandinavian cattle.
Piel anilina efecto batique.
Ganado escandinavo.

Leather

Wijzigingen voorbehouden, laatste update 202607, de getoonde afbeeldingen zijn enkel ter illustratie

Steel finish

**RESISTANCE AND
QUALITY** UNE-EN 16139:2013

FIREPROOF UNE-EN 1021-1:2006
B.S. 5852 Part 2 Crib V
UNI 9175 M-1
California Tech.Bulletin 117
BKZ 5.2

SUSTAINABILITY FSC
ISO 14001
level® 2 certified to ANSI/BIFMA e3 Standard



2-seater sofa with upholstered seat and backrest and 4 steel legs available in different colors.

1.47 m³ 36.75 kg
51.91 Ft 81.02 Lbs

	Backrest height	Seat height	Arm height	Width	Depth
Measures (mm)	820	450	685	1,710	790
Frame	4-legged steel tube base				
Seat	Solid pine structure with polypropylene elastic straps with an upholstered cushion with flexible fire resistant polyurethane foam with density between 25 kg/m ³ and 40 kg/m ³ .				
Back	Solid pine structure with polypropylene elastic straps with an upholstered cushion with flexible fire resistant polyurethane foam with density between 25 kg/m ³ and 40 kg/m ³ .				
Arms	Estructura de madera maciza de pino con cincha elástica de polipropileno recubierto de espuma flexible ignífuga de densidad entre 25kg/m ³ y 40kg/m ³ .				
Accessories	USB charging system in upholstery, personalize inner seam				
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.				
Upholstery	Leather / Piel L1 High grade cow leather Piel de vaca de 1ª categoría L3 Polished full grain leather Plena flor pulida L6 Aniline leather batique-effect. Scandinavian cattle. Piel anilina efecto batique. Ganado escandinavo.				
Leather					

Wijzigingen voorbehouden, laatste update 202607, de getoonde afbeeldingen zijn enkel ter illustratie

Steel finish

**RESISTANCE AND
QUALITY** UNE-EN 16139:2013

FIREPROOF UNE-EN 1021-1:2006
B.S. 5852 Part 2 Crib V
UNI 9175 M-1
California Tech.Bulletin 117
BKZ 5.2

SUSTAINABILITY FSC
ISO 14001
level® 2 certified to ANSI/BIFMA e3 Standard



3-seater sofa with upholstered seat and backrest and 4 steel legs available in different colors.

 2.13 m³
 75.22 Ft
  50 kg
 110.23 Lbs

	Backrest height	Seat height	Arm height	Width	Depth
Measures (mm)	820	450	685	2,470	790
Frame	4-legged steel tube base				
Seat	Solid pine structure with polypropylene elastic straps with an upholstered cushion with flexible fire resistant polyurethane foam with density between 25 kg/m ³ and 40 kg/m ³ .				
Back	Solid pine structure with polypropylene elastic straps with an upholstered cushion with flexible fire resistant polyurethane foam with density between 25 kg/m ³ and 40 kg/m ³ .				
Arms	Estructura de madera maciza de pino con cincha elástica de polipropileno recubierto de espuma flexible ignífuga de densidad entre 25kg/m ³ y 40kg/m ³ .				
Accessories	USB charging system in upholstery, personalize inner seam				
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.				
Upholstery	Leather / Piel L1 High grade cow leather Piel de vaca de 1ª categoría L3 Polished full grain leather Plena flor pulida L6 Aniline leather batique-effect. Scandinavian cattle. Piel anilina efecto batique. Ganado escandinavo.				
Leather					

Wijzigingen voorbehouden, laatste update 202607, de getoonde afbeeldingen zijn enkel ter illustratie

Steel finish

**RESISTANCE AND
QUALITY** UNE-EN 16139:2013

FIREPROOF UNE-EN 1021-1:2006
B.S. 5852 Part 2 Crib V
UNI 9175 M-1
California Tech.Bulletin 117
BKZ 5.2

SUSTAINABILITY FSC
ISO 14001
level® 2 certified to ANSI/BIFMA e3 Standard



Lounge chair with upholstered seat and backrest and 4 steel legs available in different colors.

0.8 m³ 28.25 Ft 24.9 kg 54.9 Lbs

	Backrest height	Seat height	Arm height	Width	Depth
Measures (mm)	820	450	685	920	790
Frame	4-legged steel tube base				
Seat	Solid pine structure with polypropylene elastic straps with an upholstered cushion with flexible fire resistant polyurethane foam with density between 25 kg/m ³ and 40 kg/m ³ .				
Back	Solid pine structure with polypropylene elastic straps with an upholstered cushion with flexible fire resistant polyurethane foam with density between 25 kg/m ³ and 40 kg/m ³ .				
Arms	Estructura de madera maciza de pino con cincha elástica de polipropileno recubierto de espuma flexible ignífuga de densidad entre 25kg/m ³ y 40kg/m ³ .				
Accessories	USB charging system in upholstery, personalize inner seam				
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.				
Upholstery	Leather / Piel L1 High grade cow leather Piel de vaca de 1ª categoría L3 Polished full grain leather Piena flor pulida L6 Aniline leather batique-effect. Scandinavian cattle. Piel anilina efecto batique. Ganado escandinavo.				
Leather					

Wijzigingen voorbehouden, laatste update 202607, de getoonde afbeeldingen zijn enkel ter illustratie

Steel finish

**RESISTANCE AND
QUALITY** UNE-EN 16139:2013

FIREPROOF UNE-EN 1021-1:2006
B.S. 5852 Part 2 Crib V
UNI 9175 M-1
California Tech.Bulletin 117
BKZ 5.2

SUSTAINABILITY FSC
ISO 14001
level® 2 certified to ANSI/BIFMA e3 Standard